



SLS 02P


#### **Characteristics**





- hygienic flush
- vandal-proof
- is destined for cold and hot water, temperature is regulated by mixer
- water flows after soft push of the piezo button
- water stops flowing after adjustable flowing time (can be set in 10 s - 310 s), standard 120 s
- water could be stopped by follow-up soft push of piezo button
- monitoring of battery capacity (for models with index B)
- parameter adjustment using by the remote control SLD 04

## **Installation Drawing**



- 1 water supply
- 2 stainless steel cover with electronics
- 3 mounting box
- 4 piezo button
- 5 mixer
- 6 water outlet
- 7 power supply
- 8 shower head (it is not included)



## **Technical Specification**

Stainless steel cover dimension Mounting box dimension

Operating voltage
- SLS 02P

■ SLS 02PB

Power input

operating by 24 V DC

operating by 6 V

**Battery life** 

 4 pcs. AA alkaline batteries AA, 1,5 V, 2700 mAh

Recommended flow pressure Rate of flow

Water inlet
Water outlet

170 x 170 x 10 mm 150 x 160 x 65 mm

24 V DC 6 V

0 0

7 W 3 W

approx. 2 years (100 uses per day) 0,1 - 0,6 MPa 12 l/min. (inf. data) male thread G 3/4" male thread G 3/4"

# **Supply Specification**

SLS 02P - Supply No. 12022 SLS 02PB - Supply No. 12023 stainless steel cover with electronics, stainelss steel mounting box with brass screw coupling, electromagnetic valve, ball valve and mixer, 4 pcs. AA alkaline batteries 1,5 V 2700 mAh (SLS 02PB)

### **Recommended Accessories**

SLZ 01Y	-	Supply No. 05012	power supply 24 V DC for operating of max. 5 pcs. of showers
SLZ 01Z	-	Supply No. 05011	power supply 24 V DC for operating of max. 9 pcs. of showers
SLZ 04Y	-	Supply No. 05042	power supply 24 V DC for DIN rail, for operating of max. 5 pcs. of showers
SLZ 04Z	-	Supply No. 05041	power supply 24 V DC for DIN rail, for operating of max. 9 pcs. of showers
SLZ 04X	-	Supply No. 10049	power supply 24 V DC for DIN rail, for operating of max. 15 pcs. of showers
<b>SLZ 06</b>	-	Supply No. 05060	power supply 24 V DC for operating of max. 1 pcs. of showers
SLD 04	-	Supply No. 07040	remote control for an adjustment of parameters
<b>SLA 03</b>	-	Supply No. 06030	vandal-proof shower head with possibility to set an angle of water flow
<b>SLA 13</b>	-	Supply No. 06130	vandal-proof shower head with possibility to set an angle of water flow
<b>SLA 14</b>	-	Supply No. 06140	vandal-proof shower head
<b>SLA 39</b>	-	Supply No. 06390	vandal-proof shower head
<b>SLA 40</b>	-	Supply No. 06400	vandal-proof shower head with possibility to set an angle of water flow
<b>SLA 36</b>	-	Supply No. 06360	set of 4 pcs. alkaline batteries AA, 1,5 V, 2700 mAh (for models with index B)