# Ceramic Urinal with the Radar Flushing Unit SLP 31RS





**SLP 31 - LIVO** 

# **Characteristics**

- includes Bluetooth control (Sanela Control app available for download)
- economy flushing by 1 liter of water
- easy installation by the help of paper drill template
- whole flushing unit is placed behind the urinal
- system reacts only on the direct use of the urinal (it analyses changes, which are proceeded inside of the urinal, when a liquid is flowing through)
- adjustable flushing time 0,5 15,5 s
- parameter setting and communication with the electronics via the Sanela Control app (Bluetooth) or the SLD 04 remote control (acoustic indication of setting) without dismantling the urinal
- automatic flushing after each 6 hours non-use
- monitoring of battery capacity (for models with index B)
- possibility to regulate a water flow by the ball valve
- radar flushing unit recharges a water to the siphon after each flushing

# **Technical Specification**

# **Operating voltage**

SLP 31RS
<ul> <li>SLP 31RZ</li> </ul>
SLP 31RB
Power input
operating by 24 V DC
<ul> <li>operating by 6 V</li> </ul>
Recommended flow pressure
Rate of flow
Water inlet
Water outlet

24 V DC 230 V AC/50 Hz 6 V

**Installation Drawing** 

- 1 water outlet Ø 50 mm 2 - holes for fitting
- 3 water supply

**SLP 31** 

D

60

С

255

\* for the height of the front edge of the urinal 650 mm above the floor

В

310

Α

390

4 - power supply 24 V DC or 230 V AC

F

110

G

80

н

210

Т

20

5 - holes for wall plugs

Ε

45

### 24 V DC Power • oper • oper • oper

## 8 W 3 W 0,1 - 0,6 MPa 18 l/min (inf. data) male thread G 1/2" inlet fitting with a rubber sealing



# **Supply Specification**

**Dimensions (mm)** 

**SLP 31 - LIVO** 

 SLP 31RS
 Supply No. 11315
 o

 SLP 31RZ
 Supply No. 01315
 r

 SLP 31RB
 Supply No. 11317
 r

ceramic urinal with the radar flushing unit including Bluetooth module on the mounting rail, electromagnetic valve, connecting hoses, angle valve with filter and check valve, inlet fitting with a rubber seal, siphon, mounting set, paper drill template, power supply (SLP 31RZ), 4 pcs. AA alkaline batteries 1,5 V, 2700 mAh with battery case (SLP 31RB)

# **Radar Urinal Flushing Units**

# **Recommended Accessories**

SLZ 01YSupply No. 05012power supply 24 V DC for operating of max. 5 pcs. of flushing unitsSLZ 01ZSupply No. 05011power supply 24 V DC for operating of max. 9 pcs. of flushing unitsSLZ 04ZSupply No. 05041power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing unitsSLZ 04ZSupply No. 05041power supply 24 V DC on DIN rail, for operating of max. 9 pcs. of flushing unitsSLZ 04ZSupply No. 05041power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing unitsSLZ 04ZSupply No. 05040power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing unitsSLZ 04ZSupply No. 05060power supply 24 V DC on DIN rail, for operating of max. 15 pcs. of flushing unitsSLA 11Supply No. 05060remote control for an adjustment of parametersSLA 11ASupply No. 06112deodorising urinal screen - orange colour, mango scentSLA 11BSupply No. 06113deodorising urinal screen - transparent colour, honeysuckle scentSLA 36Supply No. 06300set of 4 pcs. alkaline batteries AA 1,5 V, 2700 mAh (for models with index B)available for download on the App Store and Play Store
--